

# Square Pure 84

## Energy efficiency

Thermal Transmission Coefficient  
 **$U_w$  from 0.74 (W/m<sup>2</sup>K)**

*Please consult typology, dimensions and glazing.*

## Acoustic insulation

Triple glazing: **46,5 mm thickness**  
Maximum acoustic insulation: **Rw = 46 dB**

## Categories achieved at test centre

*Protection against atmospheric agents*

Air permeability (UNE-EN 12207):

Water tightness (UNE-EN 12208):

Wind resistance (UNE-EN 12210):

*Reference test window 1.23 x 1.48 m. 2 sashes.*

Class 4

Class E2250

Class C5

### SECTIONS

Frame 84 mm

Sash 84 mm

### CLASSIFICATION

Profile thickness Class A – nominal thickness 3,0 mm

Weather Severe weather

Impact Class II

### MAXIMUM DIMENSIONS

Width (L) 550-1400 mm

Height (H) 600-2200 mm

### MAXIMUM WEIGHT/SASH

Window 130 Kg

Balcony 130 Kg

*Please consult maximum dimensions according to types.*

### GASKETS

EPDM Triple GASKET

### OPENING POSIBILITIES

INWARDS Side hung, turn&tilt, parallel tilt, tilt, bottom hung.

### FINISHES

White

Gecodur®-lacqued

Minimalistic view – perfectly square inside view WITHOUT glazing beads (except for fixed windows) / square external view (possibility to have only 25 to 30 mm visible profile on all sides) – hidden sashes.



